

MDW-Fixed Speed Screw Air Compressor												
Power KW/HP	Pressure MPa	Air Delivery m³/min	Exhaust Temperature	Lubricating Oil L	Cooling	Compression Level	Noise db(A)	Voltage V/PH/HZ	Weight KG	Dimensions (L*W*H) mm	Outlet Diameter imch/mm	Picture
7.5KW/10HP	0.8	1.1	≤Ambient temperature +15°C	12	Air Cooling	Single stage	62±	380V/50HZ	190	800*700*930	RP1/2	
11KW/15HP	0.8	1.6	≤Ambient temperature +15°C	18	Air Cooling	Single stage	68±	380V/50HZ	300	1080*750*1000	RP3/4	
15KW/20HP	0.8	2.2	≤Ambient temperature +15°C	18	Air Cooling	Single stage	68±	380V/50HZ	300	1080*750*1000	RP3/4	
22KW/30HP	0.8	6.2	≤Ambient temperature +15°C	18	Air Cooling	Single stage	68±	380V/50HZ	460	1380*850*1160	RP1	

30KW/40HP	0.8	7.5	≤Ambient temperature +15°C	18	Air Cooling	Single stage	68±	380V/50Hz	740	1150*900*1330	RP1	
37KW/50HP	0.8	6.2	≤Ambient temperature +15°C	30	Air Cooling	Single stage	68±	380V/50Hz	780	1500*1000*1330	RP1	
45KW/60HP	0.8	7.7	≤Ambient temperature +15°C	65	Air Cooling	Single stage	68±	380V/50Hz	1060	1600*1000*1360	RP1/2	
55KW/75HP	0.8	9.1	≤Ambient temperature +15°C	30	Air Cooling	Single stage	68±	380V/50Hz	1190	1900*1250*1470	RP2	
75KW/100HP	0.8	12.6	≤Ambient temperature +15°C	65	Air Cooling	Single stage	72±	380V/50Hz	1380	2100*1400*1580	RP2	

